

# SUMMARY INFORMATION SHEET

## FLORIDA SOLAR ENERGY CENTER

1679 CLEARLAKE ROAD, COCOA, FLORIDA 32922-5703 (321) 638-1000



February 2004  
FSEC # 00101C

### MANUFACTURER

Beijing Sunda Solar Energy Technology Co. Ltd.  
No. 3 Hua Yuan Road, Haidian District,  
Beijing, China 100083

### Collector Model

SEIDO1-16

This solar collector was evaluated by the Florida Solar Energy Center (FSEC) in accordance with prescribed methods and was found to meet the minimum standards established by FSEC. This evaluation was based on solar collector tests performed at the Florida Solar Energy Center, Cocoa, Florida. The purpose of the tests is to verify initial performance conditions and quality of construction only. The resulting certification is not a guarantee of long term performance or durability.

### DESCRIPTION

Gross Length	2.127 meters	6.98 feet
Gross Width	1.880 meters	6.17 feet
Gross Depth	0.114 meters	0.37 feet
Gross Area	3.994 square meters	42.99 square feet
Transparent Frontal Area	3.619 square meters	38.96 square feet
Volumetric Capacity	1.1 liters	0.3 gallons
Weight (empty)	100.2 kilograms	221.0 pounds
Recommended Flow Rate	36 ml/s	0.6 gpm
Test Pressure	1000 kPag	145 psig
Number of Cover Plates	One	
Flow Pattern	Series	Forced circulation
Number of Flow Tubes	Sixteen	

### MATERIALS

Enclosure	Aluminum header/heat exchanger; Stainless steel frame
Glazing	Evacuated glass tubes, 0.25 cm thick
Absorber	Aluminum fins with integral copper tubes
Absorber Coating	Selective coating
Insulation	Evacuated tube, 10.1 cm wide; Polyurethane, 2.8 cm thick

### THERMAL PERFORMANCE

Tested per ASHRAE 93-1986

$$\text{Incident Angle Modifier } 5J'' = 1.0 - 0.08 \left( \frac{1}{\cos\theta} - 1 \right)$$

Efficiency Equations

$$0 = 53.7 - 170 (Ti-Ta)/I$$

$$0 = 53.0 - 30 (Ti-Ta)/I$$

$$0 = 52.6 - 139 (Ti-Ta)/I - 321 [(Ti-Ta)/I]^2$$

$$0 = 52.6 - 25 (Ti-Ta)/I - 10 [(Ti-Ta)/I]^2$$

Units of (Ti-Ta)/I are °C / Watt/m<sup>2</sup>

Units of (Ti-Ta)/I are °F / Btu/hrft<sup>2</sup>

### RATING

The collector has been rated for energy output on measured performance and an assumed standard day. Total solar energy available for the standard day is 5045 Watt-hours/m<sup>2</sup> (1600 Btu/ft<sup>2</sup>) distributed over a 10 hour period.

Output energy ratings for this collector based on the second-order efficiency curve are:

#### Collector Temperature

#### Energy Output

Low Temperature, 35°C (95°F)

36,700 Kilojoules/day

34,800 Btu/day

Intermediate Temperature, 50°C (122°F)

33,500 Kilojoules/day

31,800 Btu/day

High Temperature, 100°C (212°F)

22,100 Kilojoules/day

21,000 Btu/day

REFERENCE 00100